

X1

3.0T~5.0T

SINGLE PHASE INVERTERS From Solax



www.solaxpower.com

X1-3.0T~5.0T DUAL MPPT

The X1-3.0T~5.0T series are a high quality dual MPPT inverter offering efficiency and reliability at an unbeatable cost.

Solax have developed a range of single phase inverters, unrivaled in the industry for their quality, reliability and efficiency. The Solax single phase inverters boast a wide MPPT voltage range to allow for more energy harvesting and have a maximum input voltage of 600V, with a maximum efficiency of 97.8%.



X1-3.0T~5.0T

- > MPPT efficiency up to 99.9%
- > Maximum efficiency up to 97.8%
- > Dual MPPT tracker and wide MPPT voltage range
- > Fanless, quiet and low maintenance
- > Multiple protections
- > Multi-lingual display
- > "Plug and play" for easy installation
- > Load control via RF device (optional)



Smart Plug is the latest accessory kit from Solax Power, it enables the user to achieve complete remote control functionality through a single device. The smart plug is simply connected to the desired device which then enables remote control from the Solax app.

Get in touch now:

Global: +86 571-56260008

DE: +49 7231 4180999

Aus: +61 1300 476529

UK: +44 845 6896009

Website: www.solaxpower.com

Email: info@solaxpower.com



X1-3.0T~5.0T FROM SOLAX

SINGLE-PHASE INVERTERS-PRODUCT DATA



X1-3.0-T X1-3.3-T X1-3.6-T X1-4.2-T X1-4.6-T X1-5.0-T

INPUT (DC)						
Max.recommended DC power [W]	3250	3500	4000	4600	5200	5200
Max.DC voltage [V]	600					
Norminal DC operating voltage [V]	360					
Max. input current [A]	12/12	12/12	12/12	12/12	12/12	12/12
Max. short circuit current [A]	15/15	15/15	15/15	15/15	15/15	15/15
MPPT voltage range [V]	125-580	125-580	125-580	125-580	125-580	125-580
MPPT voltage range (full load) [V]	150-550	150-550	160-550	190-550	220-550	220-550
Start input voltage [V]	100	100	100	100	100	110
Start output voltage [V]	150	150	150	150	150	150
Shut down input voltage [V]	70	70	70	70	70	70
No. of MPP trackers	2	2	2	2	2	2
Strings per MPP tracker	1	1	1	1	1	1
OUTPUT (AC)						
Norminal AC power [VA]	3000	3300	3680	4200	4600	4600(4999 for AU)
Max. apparent AC power [VA]	3000	3300	3680	4200	4600	5000(4999 for AU)
Rated grid voltage(AC voltage range) [V]	220/230/240(180 to 280)					
Rated grid Frequency(AC frequency range) [Hz]	50(45 to 55)/60(55 to 65)					
Max. output current [A]	14	15	16	19	21	21
Displacement power factor	0.8 overexcited to 0.8 underexcited					
Total harmonic distortion(THD) [%]	<2					
EFFICIENCY						
MPPT efficiency [%]	99.90	99.90	99.90	99.90	99.90	99.90
Euro-efficiency [%]	97.00	97.00	97.00	97.00	97.00	97.00
Max. efficiency [%]	97.80	97.80	97.80	97.80	97.80	97.80
POWER CONSUMPTION						
Input standby power[W]	<2					
STANDARD						
Safety	IEC62109-1/-2/AS3100					
EMC	EN61000-1/EN61000-2/EN61000-3					
Certification	G83/2;G59;AS4777.2-2015;VDE4105; EN50438;CQC;VDE0126					
ENVIRONMENT LIMIT						
Protection class	IP65					
Operating temperature range [°C]	-20..... +60 (derating at +45)					
Humidity [%]	0-95 (non-condensing)					
Altitude [m]	<2000					
Storage temperature [°C]	-20..... +60					
Noise emission(typical) [dB]	<25					
Mounting	Wall hanging					
OTHERS						
Dimensions(WxHxD) [mm]	339x420x143					
Weight [kg]	14.6	14.6	14.6	16.7	16.7	16.7
Cooling concept	Natural					
Topology	Transformerless					
Communication	WIFI(optional), RF(optional), Meter(optional), RS485, USB, DRM					
LCD display	7 LCD					
Button	4(CapSense Button)					
Standard warranty [years]	5 (10 optional)					